

## Description

**Polypropylene 3620WZ** is engineered with nucleation to provide fast cycle time and improve contact clarity in thin wall multi-cavity molds.

**Antistat:** 3620WZ contains an antistat that will help protect molded parts from dust accumulation.

**Regulatory:** 3620WZ has passed USP Class VI testing, an all ingredients meet the chemical registration requirements of TSCA (U.S.) and DSL (Canada). TOTAL Polypropylene 3620WZ complies with all applicable FDA regulations for food contact applications.

**Recommended Applications:** 3620WZ is particularly well suited for caps, closures, medical syringes and thin wall containers.

**Processing** 3620WZ resin processes on conventional injection molding equipment with typical melt temperatures of 390-450°F (200-232°C)

## Characteristics

	Method	Unit	Typical Value
<b>Rheological Properties</b>			
Melt Flow	D-1238 Condition "L"	g/10 min	12
<b>Mechanical Properties</b>			
Tensile	D-638	psi (MPa)	5,400 (35.9)
Elongation	D-638	%	10
Tensile Modulus	D-638	psi (MPa)	250,000 (1,380)
Flexural Modulus	D-790	psi (MPa)	230,000 (1,206)
Izod Impact @ 73°F			
Notched	D-256A	ft.-lbs/in. (J/m)	0.5 (26.7)
Unnotched			16.0 (850)
Hardness	D-785A	Rockwell R	107
<b>Thermal Properties<sup>(1)</sup></b>			
Melting Point	DSC <sup>(2)</sup>	°F (°C)	330 (165)
Heat Deflection	D-648	°F @ 66 psi	260
		°C @ 4.64 kg/cm <sup>2</sup>	127
<b>Other Physical Properties</b>			
Density	D-1505	g/cc	0.905

(1) Data developed under laboratory conditions and are not to be used as specification, maxima or minima.

(2) MP determined with a DSC-2 Differential Scanning Calorimeter. Test procedure available upon request.

3620WZ 3/2015



TOTAL PETROCHEMICALS & REFINING USA, INC.  
 POLYMERS AMERICAS  
[www.totalrefiningchemicals.com](http://www.totalrefiningchemicals.com)  
 1201 Louisiana Street  
 Suite 1800  
 Houston, TX 77002

TECHNICAL CENTER  
 P.O. Box 1200  
 Deer Park, Texas 77536  
 Phone: 281-884-7500

**1-800-344-3462**